

# ARROWHEAD CERAMIC PULLEY INFORMATIONAL CHARTS



## TILE STATS

### ARROWHEAD RUBBER LAGGING INFORMATION

Description	Part Number	Wt. LBS.
½" Thick x 10" x 21.33' Drive Lagging	ASG-10X21.33-1/2-TRL	42
¾" Thick x 10" x 21.33' Drive Lagging	ASG-10X21.33-3/4-TRL	60
½" Thick x 10" x 21.33' Non-Drive Lagging	ASG-10X21.33-1/2-TRL-PLN	48
½" Thick x 10" x 21.33' Drive Lagging MSHA	ASG-10X21.33-1/2-MSHA-TRL	42
¾" Thick x 10" x 21.33' Drive Lagging MSHA	ASG-10X21.33-3/4-MSHA-TRL	56
½" Thick x 10" x 21.33' Non-Drive Lagging MSHA	ASG-10X21.33-1/2-MSHA-PLN	42

## PART NUMBERS WITH DIMENSIONS

### ARROWHEAD CERAMIC LAGGING INFORMATION

Part Number	Belt Width	BW mm	Inches Ceramic	mm Ceramic	Inches Rubber	mm Rubber
ASG-10X24-CL	24"	600	23"	587	39.25"	1016
ASG-10X30-CL	30"	750	30.50"	775	46.50"	1175
ASG-10X36-CL	36"	900	35.25"	902	51.75"	1327
ASG-10X42-CL	42"	1050	42.75"	1025	59.50"	1455
ASG-10X48-CL	48"	1200	47.50"	1215	63.375"	1629
ASG-10X54-CL	54"	1350	55.00"	1403	71.00"	1787
ASG-10X60-CL	60"	1500	57.25"	1594	76.25"	1981
ASG-10X72-CL	72"	1800	70.00"	1778	88.25"	2187
ASG-10X84-CL	84"	2150	79.25"	2222	98.25"	2642

*Ceramic + 17 = Total Length*

# ARROWHEAD CERAMIC PULLEY INFORMATIONAL CHARTS



## STRIP CALCULATION

### ARROWHEAD CERAMIC LAGGING INFORMATION

Pulley Diameter	Number of Strips
12"	4
14"	5
16"	6
18"	6
20"	7
22"	7
24"	8
26"	9
28"	9
30"	10
32"	11
34"	11
36"	12
38"	12
40"	13
42"	14
48"	16
54"	17
60"	19