

V-PLOW XD™

Mine Duty Secondary Belt Cleaner

ASGCO®

Complete Conveyor Solutions

V-Plow XD™ belt cleaner is designed for the toughest mining environments. They reduce build-up on the tail and take-up pulleys to improve belt alignment problems and thus reduce belt edge damage within the conveyor system.

Designed for the toughest mine duty environments.



V-PLOW XD™ (RUBBER) - built of a rugged steel structure to hold up in the toughest environments.

REVERSIBLE RUBBER - for double wear



Also Available in Urethane

- **Keep material from becoming trapped** - between a tail or take-up pulley and the conveyor belt.
- **Protects your belt** - from puncture damage.
- **Patent pending design** - for tough mine duty applications that can be flipped to maximize results
- **Reduces bulk material build-up** - on tail and take-up pulleys to improve belt alignment problems and thus reduce belt edge damage.
- **Simple installation** - softens the bulk material carry-back and provides gentle cleaning.
- **Equal Pressure** - and no maintenance needed, adjusts by gravity.



PRODUCT SPECIFICATIONS

Maximum Belt Speed - 1000 fpm (5.0 m/sec)

Application - Coal Fired Power Plants, Hard Rock Mining, Underground Mining, Coal Preparation Plants, Steel Mills, Iron Ore, Aggregate, Metals (copper/gold) Mining, Mineral (Phosphate, Potash, Salt) Mining, Bulk Shipping Terminals

Need Solutions... to improve efficiency, safety and productivity? **ask... ASGCO®**

www.asgco.com | 800.344.4000

ASGCO®
Complete Conveyor Solutions

V-Plow XD™ (Rubber)			
Part Number	Belt Width		Wt. Lbs.
	in	mm	
M-ASG-VP-18-1	18	450	36
M-ASG-VP-24-1	24	600	39
M-ASG-VP-30-1	30	750	50
M-ASG-VP-36-1	36	900	60
M-ASG-VP-42-1	42	1050	70
M-ASG-VP-48-1	48	1200	80
M-ASG-VP-54-1	54	1350	90
M-ASG-VP-60-1	60	1500	100
M-ASG-VP-66-1	66	1600	115
M-ASG-VP-72-1	72	1800	140
M-ASG-VP-84-1	84	2100	170
Replacement Parts (1" x 6" Rubber)			
Part Number	Belt Width		Wt. Lbs.
	in	mm	
M-ASG-5560-1X6-18-VP	18	450	5.13
M-ASG-5560-1X6-24-VP	24	600	6.72
M-ASG-5560-1X6-30-VP	30	750	8.49
M-ASG-5560-1X6-36-VP	36	900	10.08
M-ASG-5560-1X6-42-VP	42	1050	11.85
M-ASG-5560-1X6-48-VP	48	1200	13.44
M-ASG-5560-1X6-54-VP	54	1350	15
M-ASG-5560-1X6-60-VP	60	1500	16.79
M-ASG-5560-1X6-66-VP	66	1650	18.36
M-ASG-5560-1X6-72-VP	72	1800	20.15
M-ASG-5560-1X6-84-VP	84	2100	23.5
M-ASG-5560-1X6-96-VP	96	2400	26.85

V-Plow XD™ (Urethane)			
Part Number	Belt Width		Wt. Lbs.
	in	mm	
M-ASG-VP-18-1-URE	18	450	36
M-ASG-VP-24-1-URE	24	600	39
M-ASG-VP-30-1-URE	30	750	50
M-ASG-VP-36-1-URE	36	900	60
M-ASG-VP-42-1-URE	42	1050	70
M-ASG-VP-48-1-URE	48	1200	80
M-ASG-VP-54-1-URE	54	1350	90
M-ASG-VP-60-1-URE	60	1500	100
M-ASG-VP-66-1-URE	66	1600	115
M-ASG-VP-72-1-URE	72	1800	140
M-ASG-VP-84-1-URE	84	2100	17
Replacement Parts (1" x 6" Urethane)			
Part Number	Belt Width		Wt. Lbs.
	in	mm	
M-ASG-URE-1X6-18-VP-1	18	450	0
M-ASG-URE-1X6-24-VP-1	24	600	0
M-ASG-URE-1X6-30-VP-1	30	750	0
M-ASG-URE-1X6-36-VP-1	36	900	0
M-ASG-URE-1X6-42-VP-1	42	1050	0
M-ASG-URE-1X6-48-VP-1	48	1200	0
M-ASG-URE-1X6-54-VP-1	54	1350	0
M-ASG-URE-1X6-60-VP-1	60	1500	0
M-ASG-URE-1X6-72-VP-1	72	1800	0
M-ASG-URE-1X6-84-VP-1	84	2100	0
M-ASG-URE-1X6-96-VP-1	96	2400	0