

NILOS® HOT VULCANIZING CEMENT



HOT VULCANIZING CEMENT FOR VULCANIZED BELT SPLICING

NILOS® Hot Vulcanizing Cement is a specially formulated one-part cement for vulcanized belt splicing. It is engineered for use as a tackifying agent for cured and uncured rubber materials.

PROPERTIES:

- Rubber Color: Black
- Base Polymer: NR/SBR Rubber
- Solids (wt.): 15-20 %
- Formula: Naphtha (60%), Heptane (25%), Rubber (15%)
- Calculated Coverage:
 - 700 gr (1.54 Lbs.) - 2.7 M² (29 ft²)
 - 3 kg (6.6 Lbs.) - 13.4 M² (144 ft²)
 - 14.5 kg (31.9 Lbs.) – 67 M² (721 ft²)
 - 170 kg (374 Lbs.) - 670 M² (7212 ft²)
- Flash Point: 7 °C (45 °F)
- Shelf Life: 6 Months at 21° C (70° F) or 12 Months at 10° C (50° F).

FEATURES AND BENEFITS

- Builds additional tack for uncured splice materials in preparation for a conveyor belt splice
- Brushable consistency for ease of application
- Good penetration into the splice materials
- Can be used with a variety of adhesive systems
- For Natural Rubber (NR), Polyisoprene (IR), Styrene Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. – Neoprene (CR) rubber belt splices



Part Number	Size	Weight		Unit
		kg	lb	
ASG-VC-VC	1 Liter	0.8	1.75	Can



LEARN MORE!



Need Solutions... to improve efficiency, safety and productivity? **ask... ASGCO®**
www.asgco.com | 800.344.4000
 @2024 ASGCO® "Complete Conveyor Solutions"

