

# VUL-CON®

## FABRIC CONVEYOR BELT TIE GUM RUBBER



### FABRIC CONVEYOR BELT TIE GUM FOR VULCANIZED BELT SPLICING

**VUL-CON® Fabric Conveyor Belt Tie Gum Rubber** is a specifically formulated uncured rubber for vulcanized conveyor belt splicing. It is engineered for use as a skim rubber replacement material for splicing fabric conveyor belts. Our Tie Gum rubber compound allows for great adhesion to bond standard RMA Grade 1 and RMA Grade 2 fabric conveyor belts.

#### PROPERTIES:

- Base Polymer: SBR Rubber
- Rubber Color: Black
- Poly Liner Color: Clear (Double-Sided)  
- Colored ends of rolls that indicate thickness
- Specific Gravity: 1.18 – 1.24 (g/cm<sup>3</sup>)
- Hardness: 60 – 70 Shore A
- Rubber Tensile: 2000 min PSI
- Rubber Elongation: 450% min (at break)
- Shelf Life: 6 Months at 70 °F (21 °C)  
or 12 Months at 50 °F (10 °C).



#### FEATURES AND BENEFITS

- Extends the durability of vulcanized splices
- Increases resistance to wear and tear on conveyor belt splices
- Removes surface contamination in standard applications with double-sided poly
- Utilizes a poly color-coding system to identify the compound
- Compatible with belt splices made of Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), and Polychloroprene (Neoprene, CR)

Part Number	Thickness	Dimensions	Weight		Unit	End of Roll Color
			kg	lbs		
ASG-VC-TG-0.040	0.040"	20" x 50'	10.9	24.00	Roll	Blue
ASG-VC-TG-0.040-39	0.040"	39" x 50'	21.3	47.00	Roll	Blue
ASG-VC-TG-0.060	0.060"	20" x 50'	16.3	36.00	Roll	Blue
ASG-VC-TG-0.060-39	0.060"	39" x 50'	31.8	70.00	Roll	Blue

#### COLORED ENDS OF ROLLS THAT INDICATE THICKNESS



LEARN MORE!



**Need Solutions...** to improve efficiency, safety and productivity? **ask... ASGCO®**

www.asgco.com | 800.344.4000

@2024 ASGCO® "Complete Conveyor Solutions"

