

VUL-CON® CLEANING SOLVENT



CLEANING SOLVENT FOR VULCANIZED BELT SPLICING

VUL-CON® Cleaning Solvent is a specially formulated industrial solvent, cleaner and degreaser. It is engineered for use on all rubber, metal, and fabric surfaces. It is ideal for cleaning the splice area before applying cement and splice materials.

PROPERTIES:

- Color: Clear
- Base Polymer: Solvent
- Solids (wt.): 0%
- Formula: Toluene (100%)
- Calculated Coverage: 16.6 M² (288 ft²)
- Flash Point: 7 °C (45 °F)
- Storage: Store in a cool, dry, well-ventilated area away from heat, direct sunlight, hot metal surfaces and all sources of ignition.

FEATURES AND BENEFITS

- Cleans and de-greases the surface for priming and tackifying
- General surface preparation of conveyor belt vulcanized splices
- Concentrated solvent
- Specially formulated for the rubber fabrication and conveyor splicing industry
- For Natural Rubber (NR), Polyisoprene (IR), Styrene Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. – Neoprene (CR) rubber belt splices



1 Quart can

1 Gallon can

Part Number	Size	Weight		Unit
		kg	lb	
M-ASG-VC-SOLV-Q	1 Quart	0.9	2.0	Can
M-ASG-VC-SOLV-G	1 Gallon	3.6	8.0	Can

LEARN MORE!



Need Solutions... to improve efficiency, safety and productivity? **ask... ASGCO®**

www.asgco.com | 800.344.4000

@2024 ASGCO® "Complete Conveyor Solutions"

