

VUL-CON®

FABRIC BELT COVER STOCK

FABRIC BELT COVER STOCK FOR VULCANIZED BELT SPLICING



VUL-CON® Fabric Belt Cover Stock is a specially formulated uncured rubber used in vulcanized conveyor belt step and finger splicing. It is engineered for use as a cover rubber replacement material when splicing fabric conveyor belts. Our abrasion resistant compound chemically bonds to cured standard RMA Grade 1 and RMA Grade 2 cover rubber for conveyor belts.

PROPERTIES:

- **Base Polymer:** SBR Rubber
- **Rubber Color:** Black
- **Poly Liner Color:** Clear (Double-Sided) Color coded label tape runs the entire length of roll to identify each product.
- **Specific Gravity:** 1.18 – 1.24
- **Hardness:** 60 – 70 Shore A
- **Rubber Tensile Strength:** 2000 psi
- **Rubber Elongation:** 450% min (at break)
- **Shelf Life:** 6 Months at 70 °F (21 °C) or 12 Months at 50 °F (10 °C)



FEATURES AND BENEFITS

- Extends the durability of vulcanized splices
- Increases resistance to wear and tear on conveyor belt splices
- Double-sided poly reduces the risk of field contamination.
- Utilizes a color-coding system to identify the compound
- Compatible with belt splices made of Natural Rubber (NR), Polyisoprene (IR), Styrene-Butadiene (SBR), Polybutadiene (BR), and Polychloroprene (Neoprene, CR)

Part Number	Thickness	Dimensions	Weight		Unit	End of Roll Color
			kg	lbs		
ASG-VC-CS-0.188	20" x 15.5'	0.188"	15.4	34.00	Roll	Green
ASG-VC-CS-0.125	20" x 25'	0.125"	16.9	37.20	Roll	Yellow
ASG-VC-CS-0.063	20" x 47'	0.063"	15.4	34.00	Roll	Red

LEARN
MORE!



Need Solutions... to improve efficiency, safety and productivity? **ask... ASGCO®**
www.asgco.com | 800.344.4000

