VUL-CON®

CLEANING SOLVENT

CLEANING SOLVENT FOR VULCANIZED BELT SPLICING

VUL-CON® Cleaning Solvent is a specially formulated industrial solvent, cleaner and degreaser. It is engineered for use on all rubber, metal, and fabric surfaces. It is ideal for cleaning the splice area before applying cement and splice materials.

PROPERTIES:

· Color: Clear

• Base Polymer: Solvent

• Solids (wt.): 0 %

• Formula: Ethyl Acetate/Cyclohexane

• Calculated Coverage: 16.6 M² (288 ft²)

• **Storage:** Store in a cool, dry, well-ventilated area away from heat, direct sunlight, hot metal surfaces and all sources of ignition.



Complete Conveyor Solutions

FEATURES AND BENEFITS

- Cleans and degreases the surface for priming and tackifying
- General surface preparation of conveyor belt vulcanized splices
- Concentrated solvent
- Specially formulated for the rubber fabrication and conveyor splicing industry
- For Natural Rubber (NR), Polyisoprene (IR), Styrene Butadiene (SBR), Polybutadiene (BR), Polychloroprene i.e. Neoprene (CR) rubber belt splices

Part Number	Size	Weight	
		kg	lb
M-ASG-VC-SOLV-Q	1 Quart	0.9	2.0
M-ASG-VC-SOLV-G	1 Gallon	3.6	8.0



